

PI 1177402

REC'D 04 JUN 2004

WIPO

PCT

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

BEST AVAILABLE COPY
This Page Blank (uspto)

June 02, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/458,489

FILING DATE: March 28, 2003

RELATED PCT APPLICATION NUMBER: PCT/US04/09620

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



N. Williams
N. WILLIAMS
Certifying Officer

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

3-310938489 .052803 1/Pro

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

PROVISIONAL APPLICATION COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION under 37 CFR 1.53(c).

DOCKET NUMBER: B01075.70039
Express Mail Label No. EV 208 517 799 US
Date of Deposit: March 28, 2003

1-5979 U.S. PRO
60/458489
03/28/03

INVENTOR(S)/APPLICANT(S)

LAST NAME	FIRST NAME	MIDDLE INITIAL	RESIDENCE (CITY AND EITHER STATE OR FOREIGN COUNTRY)
Stevens-Wright Sagon	Debbie Stephen	W.	North Andover, MA Amherst, NH

☐ Additional inventors are being named on the separately numbered sheets attached hereto.

TITLE OF THE INVENTION (280 characters max)

ELECTRODE FOR ELECTROPHYSIOLOGY CATHETER HAVING AN ECCENTRIC SURFACE

CORRESPONDENCE ADDRESS

CUSTOMER NUMBER:

23628

ENCLOSED APPLICATION PARTS (check all that apply)

- ☒ Specification - Number of Pages = 8
- ☐ Drawing(s) - Number of Sheets
- ☐ Application Data Sheet, See 37 CFR 1.76
- ☒ Return receipt postcard

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No
☐ Yes, the name of the U.S., Government Agency and the Government Contract Number are:

☐ Other:


METHOD OF PAYMENT (check all that apply)

- ☒ A check is enclosed to cover the Provisional Filing Fees.
- ☐ The Commissioner is hereby authorized to charge any additional fees or credit overpayment to Deposit Account 23/2825. A duplicate of this sheet is enclosed.
- ☐ Small Entity Status is claimed.

PROVISIONAL FILING FEE AMOUNT \$ 160.00


March 28, 2003
Date

Respectfully submitted,


James H. Morris, Reg. No. 34,681
Telephone No.: 617-720-3500

Description of Eccentric Electrode

The "Eccentric Electrode Design" has a large tissue contact surface area. This surface area is larger than the blood contact surface area of the electrode. The objective of the larger tissue contact surface area is to produce deeper ablation lesions. In addition the electrode will minimize the mass in contact with the blood. The smaller mass will assure that minimal heating occurs along the blood contact surface. Two embodiments of the design are shown below.



60458489.032803




|||
 TITLE Eccentric Electrode

From Page No. _____

Description of Eccentric Electrode

The "Eccentric Electrode Design" has a large tissue contact surface area. This surface area is larger than the blood contact surface area of the electrode. The objective of the larger tissue contact surface area is to produce deeper ablation lesions. In addition the electrode will minimize the mass in contact with the blood. The smaller mass will assure that minimal heating occurs along the blood contact surface. Two embodiments of the design are shown below.

William E. Stevens-Wright



William E. Stevens-Wright

To Page No. _____

TITLE *Eccentric Electrode*

From Page No. —




As shown in drawing

TITLE *Face*

From Page No. —

TITLE *Eccentric Electrode*

From Page No. _____



Delta E. Johnson - Wright

To Page No. 3


To Page No. _____

TITLE Eccentric Electrode Design

111

From Page No. _____

Analysis of eccentric electrode design shows that the convective flow across the tissue surface is improved with this design. This design helps to lift the catheter tubing away from tissue surface, thus improving blood flow across the tissue surface. This cooling allows more energy to be transferred into the tissue before reaching the maximum tissue temperature of 100°C . The chart below shows the relative improvement that this design offers over various other designs. The diagram below shows the offset for a 9F, 4mm electrode design.




To Page No. _____


111

TITLE Eccentric Electrode Design


From Page No. _____

Temperature and Velocity Profiles9F Can Guppy 4mm - Temperature and Velocity Profiles


30 mm/sec 25V




55 mm/sec 25V




85 mm/sec 25V




30 mm/sec 35V




55 mm/sec 35V



85 mm/sec 35V



30 mm/sec 45V



55 mm/sec 45V



85 mm/sec 45V

Dillie & Steven Wain

104450 44444 05140

TITLE *Eccentric Electrode Design*

From Page No.

Comparative

Length									
3.5mm	9F Simplified Morgan	4.93		5.30		5.65			
3.5mm	9F Radiator	5.14	4.26	5.85	10.38	5.90	4.42		
3.5mm	9F Guppy (Slim Profile)	5.00	1.42	5.60	5.66	5.85	3.54		
3.5mm	12F Simplified Morgan	6.00	21.70	6.10	15.09	6.60	16.81		
3.5mm	11F Can	5.73	16.23	6.20	16.98	6.40	13.27		
4.0mm	9F Beehive	5.50	11.56	6.00	13.21	6.10	7.96		
4.0mm	9F Can	5.63	14.20	6.00	13.21	6.10	7.96		
4.0mm	9F Can Guppy	5.73	16.23	6.00	13.21	6.10	7.96		
4.0mm	9F Can Guppy Suspended	5.23	6.09	6.00	13.21	6.30	11.50		
4.0mm	9F Gear	5.48	11.16	5.98	12.83	6.25	10.62		
4.0mm	9F Big Fins	5.30	7.51						
5.00mm	9F Distal	5.60	13.59						
6.0mm	9F Can	5.90	19.68	6.50	22.64	6.60	16.81		
6.0mm	9F Beehive			6.50	22.64				
8.0mm	9F Simplified Morgan	4.91	-0.41	5.10	-3.77				
8.0mm	9F Can	6.30	27.79	7.10	33.96	7.30	29.20		

To Page No.

Design P. 8/2/2020 10/2/2020

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.